





* Referential photo



Dimensions are in mm

Nominal Pipe Size, NPS	Outside Diameter of Flange (O)	Minimum Thickness of Flange, (tf)	Diameter of Hub (X)	Length Through Hub (Y)	Bore Minimum (B)	Diameter of Bolt Circle (W)	Diameter of Bolt Holes (inch)	Number of Bolts	Diameter of Bolts (inch)	Length of Bolts (L)			Weight Approx. (kg)
										Stud Bolts		Machine Bolts	
										1.5 mm Raised Face	Ring Joint	1.5 mm Raised Face	
1/2"	95	12.7	38	21	22.4	66.7	5/8	4	1/2	65	75	55	55
3/4"	117	14.2	48	24	27.7	82.6	3/4	4	5/8	75	90	65	65
1"	124	15.7	54	25	34.5	88.9	3/4	4	5/8	75	90	65	65
1 1/4"	133	17.5	64	25	43.2	98.4	3/4	4	5/8	85	95	70	70
1 1/2"	155	19.0	70	29	49.5	114.3	7/8	4	3/4	90	100	75	75
2"	165	20.6	84	32	62.0	127.0	3/4	8	5/8	90	100	75	75
2 1/2"	190	23.9	100	37	74.7	149.2	7/8	8	3/4	100	115	85	85
3"	210	26.9	117	41	90.7	168.3	7/8	8	3/4	110	120	90	90
3 1/2"	229	28.4	133	43	103.4	184.2	7/8	8	3/4	110	125	95	-
4"	254	30.2	146	46	116.1	200.0	7/8	8	3/4	115	125	95	95
5"	279	33.3	178	49	143.8	235.0	7/8	8	3/4	120	135	110	110
6"	318	35.1	206	51	170.7	269.9	7/8	12	3/4	120	140	110	110
8"	381	39.6	260	60	221.5	330.2	1	12	7/8	140	150	120	120
10"	444	46.0	321	65	276.2	387.4	1 1/8	16	1	160	170	140	140
12"	521	49.3	375	72	327.2	450.8	1 1/4	16	1 1/8	170	185	145	145
14"	584	52.3	425	75	359.2	514.4	1 1/4	20	1 1/8	180	190	160	160
16"	648	55.6	483	81	410.5	571.5	1 3/8	20	1 1/4	190	205	165	165
18"	711	58.7	533	87	461.8	628.6	1 3/8	24	1 1/4	195	210	170	170
20"	775	62.0	587	94	513.1	685.8	1 3/8	24	1 1/4	205	220	185	185
22"	838	65.0	641	100	564.4	743.0	1 5/8	24	1 1/2	230	255	205	-
24"	914	68.3	702	105	616.0	812.8	1 5/8	24	1 1/2	230	255	205	205

* Note : Dimensions, design and materials are subject to change without notice. Reference weights